Loft Series Vent-Free Burners





Loft Burner Systems

Loft Burners deliver a contemporary look with an artistic flair – by itself or accessorized to suit the room. Choose decorative tops and firebox liners, in reflective black or brushed stainless steel, and crushed glass in black polished, blue clear, and clear frost.

- · 18, 24 and 30-inch Vent-Free Burners up to 40,000 Btu
- · Millivolt models include an on/off switch but will operate with Empire remote controls and thermostats
- Intermittent Pilot models include a variable flame height thermostat remote control with 30 percent turndown (for vent-free installation only)
- · Special 10,000 Btu Millivolt model for bedroom applications (where allowed by code)

A vent-free Millivolt Loft Burner may also be installed as a decorative appliance in a vented fireplace to provide ambiance and light – but without the heat. In a vented installation, the burner cannot be operated by thermostat and the flue damper must be blocked open. A damper clamp is included with each Millivolt Loft burner. Because IP Loft Burners include a thermostat and may not be installed as decorative appliances, a non-thermostat remote is available.



Loft Series Burner (VFRL-24) with Stainless Steel Decorative Top (DT-24-SS). Shown in existing masonry firebox.

Loft Burner Decorative Accessories



Top Row left to right: No Decorative Options, Polished Black Decorative Top, Brushed Stainless Steel Decorative Top.

Bottom Row left to right: Blue Clear Decorative Glass, Medium Decorative Rocks and Accent Pebbles, Polished Black Decorative Glass.

(Clear Frost Decorative Glass shown on opposite page)

Decorative Media



Onyx Solid Drops One-inch



Blue Clear Crushed



Sangria Luster Droplets 1/2-inch



Glacier Ice Droplets 1/2-inch



Bronze Reflective Crushed



Clear Frost Crushed



Black Polished Crushed



Copper Reflective Crushed



Medium Rocks



Loft Series Vent-Free Multi-sided burner (VFRU-24) with Clear Frost Decorative Glass (DG-30-CLF). Shown in a Vent-Free peninsula firebox with Flush Louvers.



Accent Peobles

Vent-Free Loft Series Burners

				Non-Empire Minimum Firebox Dimensions					
Model	Description	Btu Input	Fits Empire Fireboxes	Front Width (inches)	Rear Width (inches)	Depth (inches)	Height (inches)	Ship Wt. (lb)	
On/Off Millivolt, Standing Pilot									
VFRL-18-10	Loft Burner, 18-inch	10,000	VF(D,P,S)32	28	21	13	17	13	
VFRL-18	Loft Burner, 18-inch	26,000	VF(D,P,S)32	28	21	13	17	13	
VFRL-24	Loft Burner, 24-inch	36,000	VF(D,P,S)36	34	27	13	18	15	
VFRL-30	Loft Burner, 30-inch	40,000	VF(D,P,S)42	40	33	13	20	18	
Intermittent Pilot, Includes Thermostat Variable Remote Control									
VFIL-18	Loft Burner, 18-inch	26,000	VF(D,P,S)32	28	21	13	17	14	
VFIL-24	Loft Burner, 24-inch	36,000	VF(D,P,S)36	34	27	13	18	16	
VFIL-30	Loft Burner, 30-inch	40,000	VF(D,P,S)42	40	33	13	20	18	

Vent-Free Multi-Sided Loft Series Burners

				Non-Empire Minimum Firebox Dimensions			ensions	Ship	
Model	Description	Btu Input	Fits Empire Fireboxes	Front Width (inches)	Rear Width (inches)	Depth (inches)	Height (inches)	Wt. (lb)	
On/Off Millivolt, Standing Pilot									
VFRU-24	Multi-Sided Loft Burner, 24-inch	36,000	VFP36(S,P)B	32	32	17 1/2	18	21	
Intermittent Pilot, Includes Thermostat Variable Remote Control									
VFIU-24	Multi-Sided Loft Burner, 24-inch	36,000	VFP36(S,P)B	32	32	17 1/2	18	20	

Decorative Accessories for Loft Series Burners

Burner Size	Polished Black Decorative Top	Brushed SS Decorative Top	Black Polished Decorative Glass	Blue Clear Decorative Glass	Clear Frost Decorative Glass	Medium Sized Decorative Rocks	Accent Pebbles
Standard Loft Bu	urners						
18-inch	DT-18-PB	DT-18-SS	DG-1-BKP	DG-1-BUC	DG-1-CLF	DR-1-FMA	DRFPA
24-inch	DT-24-PB	DT-24-SS	DG-1-BKP	DG-1-BUC	DG-1-CLF	DR-1-FMA	DRFPA
30-inch	DT-30-PB	DT-30-SS	DG-1-BKP	DG-1-BUC	DG-1-CLF	DR-1-FMA	DRFPA
Multi-Sided Lo	ft Burners						
24-inch	DTU-24-PB	DTU-24-SS	DG-1-BKP	DG-1-BUC	DG-1-CLF	DR-1-FMA	DRFPA

Control Accessories

Control Accessories					
Model	Description Note: Thermostats may not be used in vented applications				
FRBC	Battery Operated Remote Control – On/Off	1			
FRBTC2	Battery Operated Remote Control w/ Thermostat (not for vented applications)	1			
FREC	Electric Remote Control – On/Off	1			
FRBTPS	Programmable Remote Control, Battery Operated (not for vented applications)	2			
FWS-1	Wall Switch - On/Off	1			
TMV	Wall Thermostat, Millivolt – Reed Switch (not for vented applications)	2			
TRW	Wireless Remote Wall Thermostat	2			

Gas Inlet				
Type of Gas	Natural or Propane			
Iron Pipe Size (N.P.T.)	3/8-inch			
Ignition System	Standing Pilot/Piezo and Intermittent Pilot			

Warranty

All vented parts carry a three-year limited warranty.

All vent-free parts carry a five-year limited warranty with a five-year limited labor warranty.

All remote controls carry a one-year limited parts warranty.

Installation and Safety

Pilot equipped with automatic shut-off and Oxygen Depletion Sensor on Vent-Free Burners. Refer to your Owner's Manual for complete installation and safety information.

